

BOWMAN


Coating Measurement Instruments

L SERIES XRF

High Precision Coating Measurement System



What's Distinctive:
Chamber volume 600% larger than other units



Who Benefits

The L Series desktop XRF instrument was engineered for the diverse needs of the metal finishing industry, specifically manufacturers and contract shops who work with large fasteners, hardware, plumbing fixtures and other out-sized items.

Common Applications

- › ZnFe/Fe and ZnNi/Fe for automotive components
- › Cr/Ni/Cu/ABS for plumbing industry components
- › TiCN/WCo, TiAlN/WC for cutting tools and similar applications

Like other Bowman XRF systems, the L Series precisely and quickly determines the thickness of coatings, and the elements present in the sample. The instrument measures up to five coating layers simultaneously, any or all of which can be alloys.

Key Features

L Series XRF instruments use Bowman's proprietary micro spot focus x-ray tube as the energy source, a temperature-stabilized silicon PIN diode as the detector and a wide bandwidth, multi-channel amplifier to sort and count the radiated photons. Bowman Xralizer software employs advanced software algorithms to identify and quantify the thickness of the materials from the detected photons.

A micro focus video camera, aligned with the x-ray optics axis, identifies the area on the sample to be measured. An elevator, controlled by a focus laser, accommodates measurement samples of varying heights.

BOWMAN

1125 Remington Rd.
Schaumburg, IL 60173

› 847.781.3523
› www.bowmanxrf.com
› sales@bowmanxrf.com

© Copyright 2018 Bowman



Made
in the USA



BOWMAN L SERIES XRF

Superior technically.
Supported locally.

Specifications

X-ray Excitation

50 W (50kV and 1mA) micro-focused W anode tube

Detector

Solid state PIN detector with 190eV resolution or better

Focal Depth

Multi fixed focal depths with laser

Video Magnification

30x: Standard

45x: Optional

Working Environment:

50°F (10°C) to 104°F (40°C) and up to 98% RH, non-condensing

Weight

110kg

Programmable XY:

Table size: 10" x 10"

Travel: 10" x 10"

Element Range

Aluminum 13 to Uranium 92

Analysis layers and elements

5 layers (4 layers + base) and 10 elements in each layer.

Composition analysis of up to 25 elements simultaneously

Filters/Collimators

4 primary filters / 4 motorized collimators

Digital Pulse Processing

4096 CH digital multi-channel analyser with flexible shaping time. Automatic signal processing including dead time correction and escape peak correction

Processor:

Intel, CORE i5 3470 (3.2GHz), 8GB DDR3 Memory, Microsoft Windows 10 Prof, 64bit equivalent

Camera optics:

1/4" CMOS-1280x720 VGA resolution

Power Supply:

150W, 100~240 volts; frequency range 47Hz to 63Hz

Dimensions (HxWxD):

Internal: 280mm (11"), 550mm (22"), 600mm (24")

External: 750mm (30"), 700mm (28"), 750mm (30")

The Bowman Partner Network

Bowman's Partner Service Network was established to facilitate large multi-national projects in the PCB industry. Today, it has become the model for XRF technical service worldwide, serving board shops, electronics manufacturers, automotive and aerospace OEMs, jewelry manufacturers, and contract metal finishers in all sectors.

The Bowman Partner Network enables XRF technical service experts worldwide to provide same-day response to every service, repair and upgrade requirement.



Bowman global partners are certified annually, and maintain the highest standards of excellence and best practices.



Certificate #L2213



Made in the USA

BOWMAN

1125 Remington Rd.
Schaumburg, IL 60173

› 847.781.3523
› www.bowmanxrf.com
› sales@bowmanxrf.com

© Copyright 2018 Bowman